



10
FLAT

Sawa®

EN 13731
NFPA 1936

Erhöhte
Hubkraft

Kompatibel mit
Hebekissen 8 bar

Hochbelastbar

TECHNISCHE DATEN

TYP	ART. NR.	ABMESSUNGEN			GEWICHT	ARBEITS- DRUCK	LUFT BEDARF	MAX. TRAGKRAFT	MAX. HUBHÖHE	MAX. TRAGFÄHIGKEIT BEI MAX. HUBHÖHE
		LÄNGE	BREITE	HÖHE						
		[cm] / [inch]	[cm] / [inch]	[cm] / [inch]						
SFB-H 2.5/17	282432	45 / 18"	45 / 18"	2.5 / 1"	5.2 / 11.5	10 / 145	220 / 7.8	16.6 / 18.3	17 / 6.7"	2.5 / 2.8
SFB-H 8/17	291294	55 / 22"	55 / 22"	2.5 / 1"	7.4 / 16	10 / 145	280 / 9.9	26.4 / 29	17 / 6.7"	8.1 / 8.9
SFB-H 12/17	291295	61 / 24"	61 / 24"	2.5 / 1"	9.2 / 20	10 / 145	437.5 / 15.5	31.5 / 34.7	17 / 6.7"	11.9 / 13.1
SFB-H 25/17	291296	78 / 31"	78 / 31"	2.5 / 1"	14.5 / 32	10 / 145	650 / 23	55.8 / 61.3	17 / 6.7"	25.3 / 27.8
SFB-H 42/17	291297	91.5 / 36"	91.5 / 36"	2.5 / 1"	20.5 / 45	10 / 145	1012.5 / 35.8	80 / 88	17 / 6.7"	41.6 / 45.8

ZUBEHÖR (PASSEND NUR FÜR FLACHE HEBEKISSEN)



**DREIFACH TOTMANN-
STEUERUNG 3 EXP**
10 bar (145 psi)
4.0 kg (8.8 lbs) 609801



**SATZ DREIFACH
FLACHBEUTELVERBINDER,
ORANGE**
(4 STK. PRO SET) 0.6 kg
(1.3 lbs) 530545



**SATZ DOPPEL
FLACHBEUTELVERBINDE,
GELB (4 STK. PRO SET)**
0.4 kg (0.88 lbs) 529480

HUBHÖHE [mm] / [inch]

