

10
BAR

Sawa®



EN 13731
NFPA 1936

Erhöhte
Hubkraft

Kompatibel mit
Hebekissen 8 bar

Hochbelastbar

TECHNISCHE DATEN

TYP	ART. NR.	ABMESSUNGEN			GEWICHT	ARBEITSDRUCK	LUFT BEDRAF	MAX. HUBKRAFT	MAX. HUBHÖHE
		LÄNGE	BREITE	HÖHE					
		[cm]/ [inch]	[cm]/ [inch]	[cm]/ [inch]					
SLK-H 1	291240	15/ 6"	15/ 6"	2.5/ 1"	0.55/ 1.2	10/ 145	7/ 0.3	1.2/ 1.3	8/ 3.1"
SLK-H 4	291241	22.5/ 9"	22.5/ 9"	2.5/ 1"	1.25/ 3	10/ 145	19/ 0.7	3.3/ 3.6	13/ 5.1"
SLK-H 7	291242	30/ 12"	30/ 12"	2.5/ 1"	2 / 4	10/ 145	52/ 1.9	6.8/ 7.5	16/ 6.3"
SLK-H 12	291243	38/ 15"	38/ 15"	2.5/ 1"	3.5/ 8	10/ 145	106/ 3.8	12.1/ 13.3	21/ 8.3"
SLK-H 17	291244	45/ 18"	45/ 18"	2.5/ 1"	5 / 11	10/ 145	186/ 6.6	16.6/ 18.3	25/ 9.3"
SLK-H 26	291245	55/ 22"	55/ 22"	2.5/ 1"	7 / 15	10/ 145	362/ 12.8	26.3/ 28.9	30/ 11.8"
SLK-H 32	291246	61/ 24"	61/ 24"	2.5/ 1"	9/ 20	10/ 145	508/ 18.0	31.8/ 35	34/ 13.4"
SLK-H 41	291247	69/ 27"	69/ 27"	2.5/ 1"	11/ 24	10/ 145	759/ 26.8	41.3/ 45.4	38/ 15"
SLK-H 56	291248	78/ 31"	78/ 31"	2.5/ 1"	14.1/ 31	10/ 145	1122/ 39.7	55.8/ 61.4	42/ 16.5"
SLK-H 69	291249	87/ 34"	87/ 34"	2.5/ 1"	18.2/ 40	10/ 145	1595/ 56.4	68.7 / 75.6	47 / 18.5"
SLK-H 88	291250	94.5/ 37"	94.5 / 37"	2.6/ 1"	22.7/ 50	10/ 145	1650/ 58.3	88/ 96.8	52/ 20.5"

HUBHÖHE [mm]/ [inch]

